



# SAFETY DATA SHEET

**BOSTIK PVC CEMENT N BLUE**  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

## Section 1: Identification: Product identifier and chemical identity

### Product identifier

**Product Name** BOSTIK PVC CEMENT N BLUE

### **Product Code(s)**

30840463  
30840463; 30840464; 30840465; 30840466; 30840488

### Other means of identification

**Proper Shipping Name** Adhesives

**UN number or ID number** UN1133

**Pure substance/mixture** Mixture

### Recommended use of the chemical and restrictions on use

**Recommended use** Adhesives and/or sealants

**Uses advised against** No information available

### Details of manufacturer or importer

#### **Supplier**

Bostik Australia Pty Ltd  
51-71 High Street,  
Thomastown Victoria  
Australia  
Tel: 613 9279-9333  
Fax: 613 9279-9342

**ABN:** 79 003 893 838

**E-mail address** au-bostik-sds@bostik.com

### Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

## Section 2: Hazard(s) identification

### GHS Classification

<b>Flammable liquids</b>	Category 2 - (H225)
<b>Acute toxicity - Inhalation (Dusts/Mists)</b>	Category 4 - (H332)
<b>Skin corrosion/irritation</b>	Category 2 - (H315)
<b>Serious eye damage/eye irritation</b>	Category 1 - (H318)
<b>Specific target organ toxicity (single exposure)</b>	Category 3 - (H336)

### Label elements

Flame  
Exclamation mark

# SAFETY DATA SHEET

**BOSTIK PVC CEMENT N BLUE**  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

Corrosion



**Signal word**  
DANGER

## **Hazard statements**

H225 - Highly flammable liquid and vapor  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness  
Repeated exposure may cause skin dryness or cracking

## **Precautionary Statements - Prevention**

Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Wash face, hands and any exposed skin thoroughly after handling  
Ground and bond container and receiving equipment  
Use non-sparking tools  
Take action to prevent static discharges  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container closed  
Wear protective gloves/clothing and eye/face protection  
Keep cool  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a doctor  
IF ON SKIN: Wash with plenty of water and soap  
If skin irritation occurs: Get medical advice/attention  
Take off contaminated clothing and wash it before reuse  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
Call a doctor if you feel unwell  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

## **Precautionary Statements - Storage**

Store in well-ventilated place

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## **Other hazards which do not result in classification**

May be harmful in contact with skin.  
In use, may form flammable/explosive vapor-air mixture.

## **Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)**

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

**Poison Schedule Number** 5

## **Label requirements in accordance with SUSMP**

CAUTION  
KEEP OUT OF REACH OF CHILDREN  
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

## **Section 3: Composition and information on ingredients, in accordance with Schedule 8**

# SAFETY DATA SHEET

BOSTIK PVC CEMENT N BLUE  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

## Substance

Not applicable

## Mixture

Chemical name	CAS No	Weight-%
Methyl ethyl ketone	78-93-3	30 - 60
Cyclohexanone	108-94-1	10 - <30
Acetone	67-64-1	10 - <30
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	0 - <10
Non-hazardous ingredients	Proprietary	Balance

## Section 4: First aid measures

**Emergency telephone number** Poisons Information Center, Australia: 13 11 26  
Poisons Information Center, New Zealand: 0800 764 766

### Description of first aid measures

**General advice** Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

**Inhalation** Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.

**Eye contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical attention. Remove contact lenses, if present and easy to do. Continue rinsing.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention.

**Self-protection of the first aider** Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists.

### Most important symptoms and effects, both acute and delayed

**Symptoms** Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing. Difficulty in breathing.

### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## Section 5: Firefighting measures

### Suitable Extinguishing Media

**Suitable extinguishing media** Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

# SAFETY DATA SHEET

BOSTIK PVC CEMENT N BLUE  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

**Unsuitable extinguishing media** No information available.

## Specific hazards arising from the chemical

**Specific hazards arising from the chemical** Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**Hazardous combustion products** Carbon oxides. Carbon dioxide (CO<sub>2</sub>). Hydrogen chloride. Hydrochloric Acid.

## Special protective actions for fire-fighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

**Hazchem code** •3YE

## **Section 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapors or mists.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

### Precautions to prevent secondary hazards

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## **Section 7: Handling and storage, including how the chemical may be safely used**

### Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety

# SAFETY DATA SHEET

**BOSTIK PVC CEMENT N BLUE**  
Revision Number 2.01

**Revision date** 08-Nov-2022  
**Supersedes Date:** 12-Aug-2021

practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

## Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

**Recommended storage temperature** Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

## **Section 8: Exposure controls and personal protection**

### Control parameters

#### **Exposure Limits**

Chemical name	Australia
Methyl ethyl ketone 78-93-3	TWA: 150 ppm TWA: 445 mg/m <sup>3</sup> STEL: 300 ppm STEL: 890 mg/m <sup>3</sup>
Cyclohexanone 108-94-1	TWA: 25 ppm TWA: 100 mg/m <sup>3</sup>
Acetone 67-64-1	TWA: 500 ppm TWA: 1185 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 2375 mg/m <sup>3</sup>

#### **Biological occupational exposure limits**

### Appropriate engineering controls

**Engineering controls** Showers, eyewash stations, and ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

**Hand protection** Wear suitable gloves. Impervious gloves.

**Respiratory protection** Organic gases and vapors filter conforming to EN 14387.

# SAFETY DATA SHEET

BOSTIK PVC CEMENT N BLUE  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

Environmental exposure controls No information available.

## Section 9: Physical and chemical properties

### Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid
Color	Blue
Odor	Ketone
Odor threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	56 °C	
Flash point	-4 °C	(Methyl ethyl ketone)
Evaporation rate	No data available	
Flammability	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	11.5	
Lower flammability or explosive limits	1.8	
Vapor pressure	9.5	@ 20 °C
Relative vapor density	> 1	
Relative density	0.94	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	515 °C	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	600 900 mPa s	
Explosive properties	No information available	
Oxidizing properties	No information available	

### Other information

Solid content (%)	No information available
Liquid Density	No information available
VOC content	732 g/L

## Section 10: Stability and reactivity

### Reactivity

Reactivity No information available.

### Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

### Possibility of hazardous reactions

# SAFETY DATA SHEET

BOSTIK PVC CEMENT N BLUE  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

**Possibility of hazardous reactions** None under normal processing.

## Conditions to avoid

**Conditions to avoid** Heat, flames and sparks. Excessive heat.

## Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

## Hazardous decomposition products

**Hazardous decomposition products** Carbon oxides. Nitrogen oxides (NOx). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

## **Section 11: Toxicological information**

### Acute toxicity

### Information on likely routes of exposure

#### Product Information

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.

**Skin contact** Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Symptoms** Redness. Burning. May cause blindness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 5,070.30  
ATEmix (dermal) 3,633.50  
ATEmix (inhalation-vapor) 36.30  
ATEmix (inhalation-dust/mist) 4.95

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Cyclohexanone	=1535 mg/kg (Rattus)	= 947 mg/kg (Oryctolagus cuniculus)	=8000 ppm (Rattus) 4 h
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
bis-[4-(2,3-epoxipropoxy)phenyl]propane	=11300 µL/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-

# SAFETY DATA SHEET

BOSTIK PVC CEMENT N BLUE  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

See section 16 for terms and abbreviations

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** May cause skin irritation. Classification based on data available for ingredients. Causes skin irritation.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

Component Information					
Methyl ethyl ketone (78-93-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

**Respiratory or skin sensitization** No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	No sensitization responses were observed

Acetone (67-64-1)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	Not a skin sensitizer

**Germ cell mutagenicity** No information available.

## Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Cyclohexanone 108-94-1			Group 3
bis-[4-(2,3-epoxipropoxy)phenyl]propane 1675-54-3			Group 3

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause drowsiness or dizziness. May cause respiratory irritation.



# SAFETY DATA SHEET

**BOSTIK PVC CEMENT N BLUE**  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## Section 12: Ecological information

### Ecotoxicity

#### Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna )
Cyclohexanone 108-94-1	EC50: =20mg/L (96h, Chlorella vulgaris)	LC50 96 h 481 - 578 mg/L (Pimephales promelas flow-through)	EC50 = 18.5 mg/L 5 min EC50 = 21.3 mg/L 10 min EC50 = 25 mg/L 5 min	EC50: =800mg/L (24h, Daphnia magna)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
bis-[4-(2,3-epoxipropoxy)phenyl]propane 1675-54-3	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.5 mg/l 96Hr (Oncorhynchus mykiss) (OECD 203)	-	LD50 (48h) =2.7 mg/L (Daphnia magna) (OECD 202)

### Persistence and degradability

**Persistence and degradability** No information available.

#### Component Information

##### Methyl ethyl ketone (78-93-3)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

##### Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

### Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

#### Component Information

Chemical name	Partition coefficient
Methyl ethyl ketone 78-93-3	0.3
Cyclohexanone 108-94-1	1.05
Acetone	-0.24

# SAFETY DATA SHEET

BOSTIK PVC CEMENT N BLUE  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

67-64-1	
bis-[4-(2,3-epoxipropoxy)phenyl]propane 1675-54-3	3.78

## Mobility

**Mobility in soil** No information available.

**Mobility** No information available.

## Other adverse effects

**Other adverse effects** No information available.

Chemical name	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disrupters - Evaluated Substances	Endocrine disrupting potential
bis-[4-(2,3-epoxipropoxy)phenyl]propane 1675-54-3	Group II Chemical	-	-

## **Section 13: Disposal considerations**

### Disposal methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

## **Section 14: Transport information**

### ADG

**UN number or ID number** UN1133  
**UN proper shipping name** Adhesives  
**Transport hazard class(es)** 3  
**Packing group** II  
**Special Provisions** \*  
**Limited quantity (LQ)** 5 L  
**Description** UN1133, Adhesives, 3, II

**Hazchem code** •3YE

### IATA

**UN number or ID number** UN1133  
**Transport hazard class(es)** 3  
**Packing group** II  
**ERG Code** 3L  
**Special Provisions** A3  
**Limited quantity (LQ)** 1 L  
**Description** UN1133, Adhesives, 3, II

### IMDG

**UN number or ID number** UN1133  
**Transport hazard class(es)** 3  
**Packing group** II  
**EmS-No** F-E, S-D  
**Limited Quantity (LQ)** 5 L  
**Marine pollutant** NP  
**Description** UN1133, Adhesives, 3, II, (-4°C c.c.)

# SAFETY DATA SHEET

**BOSTIK PVC CEMENT N BLUE**  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
No information available

## Section 15: Regulatory information

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

### National regulations

#### Australia

See section 8 for national exposure control parameters

#### **Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)**

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

**Poison Schedule Number** 5

#### **Major hazard (accident/incident planning) regulation**

Verify that license requirements are met

#### Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III  
Liquids with flash points <61°C kept above their boiling points at ambient conditions

#### Threshold quantity (T)

50 000  
200

#### **National pollutant inventory**

Subject to reporting requirement

<b>Chemical name</b>	<b>National pollutant inventory</b>
Methyl ethyl ketone 78-93-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Cyclohexanone 108-94-1	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Acetone 67-64-1	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

#### **International Inventories**

**AIIC** Listed  
**NZIoC** Listed  
**ENCS** Listed  
**IECSC** Listed  
**KECL** Listed  
**PICCS** Listed

#### **Legend:**

**AIIC** - Australian Inventory of Industrial Chemicals

# SAFETY DATA SHEET

**BOSTIK PVC CEMENT N BLUE**  
Revision Number 2.01

Revision date 08-Nov-2022  
Supersedes Date: 12-Aug-2021

**NZIoC** - New Zealand Inventory of Chemicals  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

## International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

## Europe

### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorization:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **2015/863/EU - RoHS**

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

## **Section 16: Any other relevant information**

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 08-Nov-2022

#### **Revision Note**

\*\*\*Indicates updated data since last publication.

## **Key or legend to abbreviations and acronyms used in the safety data sheet**

### **Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

### **Section 11: TOXICOLOGICAL INFORMATION**

LD50 (lethal dose)

### **Section 12: Ecological information**

EC50 (effective concentration)

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**